

# MATERIAL SAFETY DATA SHEET

Page 1 of 4

## SPARKL SEAL

<b>1. Product And Company Identification</b>	
<b>Manufacturer</b> NOX-CRETE MANUFACTURING INC 1444 SOUTH 20TH STREET OMAHA, NE 68108	<b>Contact Information</b>  FAX Number: 402-341-9752 E-Mail: corporate@nox-crete.com Web Site: www.nox-crete.com
<b>Emergency Phone Number</b> CHEMTREC: 800-424-9300 CHEMTREC OUTSIDE OF U.S.: 703-527-3887	<b>Manufacturer Phone Number</b> 402-341-2080
Issue Date: 06/14/2012 Product Name: SPARKL SEAL Chemical Family: CONCRETE CURING AND SEALING COMPOUNDS MSDS Number: 100 Product Code: SP	

<b>2. Hazards Identification</b>
<b>Primary Routes(s) Of Entry</b> Eye Contact, Ingestion, Inhalation, Skin Contact
<b>Eye Hazards</b> May cause extreme irritation, burns and corneal injury.
<b>Skin Hazards</b> Causes skin irritation.
<b>Ingestion Hazards</b> May cause mouth, throat, esophagus and stomach irritation, nausea, vomiting and diarrhea.
<b>Inhalation Hazards</b> Causes respiratory tract irritation. May cause headache and/or drowsiness.

<b>3. Composition/Information On Hazardous Ingredients</b>			
	Ingredient Name	CAS Number	
	AROMATIC SOLVENT	64742-95-6	
	AROMATIC SOLVENT	1330-20-7	

<b>4. First Aid Measures</b>
<b>Eye</b> In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes .Get medical attention immediately if irritation develops and persists.
<b>Skin</b> Remove contaminated clothing and shoes. Wash affected areas with soap and water. Wash clothing before reuse. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.
<b>Ingestion</b> If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation</b> If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get medical attention if breathing

## SPARKL SEAL

### 4. First Aid Measures - Continued

#### Inhalation - Continued

becomes difficult or symptoms persist.

### 5. Fire Fighting Measures

**Flash Point:** 80 °F 27 °C

**Flash Point Method:** PMCC

**Flammability Class:** Flammable Liquid

#### Extinguishing Media

Use CO2 (Carbon Dioxide), dry chemical, or foam.

#### Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear. Water can be used to cool and protect exposed material. Avoid spreading burning liquid with water used for cooling purposes.

### 6. Accidental Release Measures

Eliminate any ignition source. Dike or impound spilled material. Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect into vapor tight containers and dispose of properly.

### 7. Handling And Storage

#### Handling And Storage Precautions

Keep containers tightly closed. Use only with adequate ventilation.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Eye/Face Protection

Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury.

#### Skin Protection

Wear gloves and appropriate protective clothing as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

#### Respiratory Protection

General room ventilation is normally adequate. Avoid breathing the product mist. The use of a NIOSH approved respirator is recommended whenever the airborne concentrations exceed the TLV.

#### Ingredient(s) - Exposure Limits

AROMATIC SOLVENT

25 PPM

AROMATIC SOLVENT

TWA 100ppm 8 Hours

### 9. Physical And Chemical Properties

#### Appearance

Clear liquid with strong aromatic odor.

**Chemical Type:** Mixture

**Boiling Point:** > 280 °F > 138 °C

**Specific Gravity:** Lighter than water

**Packing Density:** 7.5 lbs per gal 0.9 kg per liter

**Solubility:** Negligible

**Evaporation Rate:** Slower than ether

VOC: Less than 700 G/l

Flash Point: 80 F 27 C (PMCC)

# MATERIAL SAFETY DATA SHEET

Page 3 of 4

## SPARKL SEAL

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

**Incompatible Materials**

Sulfuric acid, nitric acid. Strong oxidizing agents.

**Hazardous Decomposition Products**

Combustion may produce carbon monoxide, carbon dioxide, and various hydrocarbon derivatives.

### 11. Toxicological Information

**Chronic/Carcinogenicity**

No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program, the U.S. Occupational Safety and Health Act, or the International Agency on Research on Cancer (IARC).

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Care must be taken to prevent environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

### 14. Transport Information

**Proper Shipping Name**

Paint Related Material,3,UN1263, PG III

**Hazard Class**

Flammable Liquid

**Freight Class**

55

### 15. Regulatory Information

**SARA Section 313 Notification**

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.


CHEMICAL	CAS #	MAX WEIGHT %
Xylene	1330-20-7	32.6
1,2,4-Trimethylbenzene	95-63-6	12.1
Ethylbenzene	100-41-4	9.4

**State Regulations**

Proposition 65: WARNING. This product contains one or more chemicals known to the State of California to cause cancer and/or reproductive toxicity.

# MATERIAL SAFETY DATA SHEET

## SPARKL SEAL

<b>NFPA</b>	<b>HMIS</b>								
	<table border="1"><tr><td>HEALTH</td><td style="text-align: center;">2</td></tr><tr><td>FLAMMABILITY</td><td style="text-align: center;">3</td></tr><tr><td>REACTIVITY</td><td style="text-align: center;">0</td></tr><tr><td>PERSONAL PROTECTION</td><td style="text-align: center;">X</td></tr></table>	HEALTH	2	FLAMMABILITY	3	REACTIVITY	0	PERSONAL PROTECTION	X
HEALTH	2								
FLAMMABILITY	3								
REACTIVITY	0								
PERSONAL PROTECTION	X								

### 16. Other Information

#### Revision/Preparer Information

MSDS Preparer: Nox-Crete Manufacturing

This MSDS Supersedes A Previous MSDS Dated: 10/19/2010

#### Reference Documentation

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyers risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

#### Disclaimer

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of this use thereof.

**NOX-CRETE MANUFACTURING INC**